

4MP Fixed-focal Wi-Fi Bullet Network Camera

DH-F4C-PV



Series Overview

The Bullet Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions, such as AI human detection, to accurately trigger alarms. Information is also synchronously sent to your phone to keep you up-to-date. With its IP67 rating, these cameras are able to withstand harsh environments, making them highly suitable for use in small and medium-sized settings such as small-sized retail stores.



4MP

Clear images with sharp details



Al Human Detection

Focuses on what matters and reduces false alarms



Smart Dual Light

Captures color details for post-event



Sound and Light Alarm

Provides instant alarms to deter intruders



Two-way Talk

Communication anytime, anywhere



IP67 Protection

Withstands harsh environments



H.265

Advanced H.265 compression technology



DMSS App

Easy to use



Micro SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.









Specifications

Camera

1/3" CMOS Image Sensor

Max. Resolution 2560 (H) × 1440 (V)

Electronic Shutter Speed Auto/Manual 1/3 s-1/100,000 s

Up to 30 m (98.53 ft) (IR) Illumination Distance

Up to 30 m (98.53 ft) (Warm light)

Illuminator On/Off Control

Illuminator Number 2 (IR LED); 2 (Warm light)

F1.6 Max. Aperture

2.8 mm: H: 98°; V: 55°; D: 115° 3.6 mm: H: 78°; V: 41°; D: 94° Field of View

Intelligence

Support the classification and accurate detection of Human Detection

Video & Audio

Video Compression H.264B; H.264; H.264H; H.265

Main stream: $2560 \times 1440@(1-25/30 \text{ fps})$; sub stream: $640 \times 480@(1-25/30 \text{ fps})$; *The values above are the max. frame rates of each stream; for multiple streams, the values will be Video Frame Rate subjected to the total encoding capacity.

4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720) Resolution

H.264: 32kbps ~ 4096kbps H.265: 12kbps ~ 4096kbps Video Bit Rate

Auto(ICR)/Color/B/W Day/Night

Motion Detection OFF/ON Smart Illumination

Tools:

Installation Position

Map×1 Mounting Plate×1

Screw Package×1

Waterproof Connector x 1 **Documents:**

QR Code×1

Quick Start Guide×1

Legal and Regulation Information×1

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker

G.711a; G.711Mu; PCM; G.726 Audio Compression

Network

Network Port RJ-45 (10/100 Base-T)

IEEE 802.11b/g/n 2.4–2.4835 GHz, 2.4 G,≤20dBm@2400-2483.5MHz Wi-Fi

Micro SD card (support max. 256 GB)

Smart PSS; DSS; DMSS Management Software

Mobile Client iOS:Android

General

Storage

CE-LVD: EN62368-1;

CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; Certifications

CE-RED: Radio Equipment Directive 2014/53/EU

Power Supply 12 VDC

Power Consumption

Basic: 2.2 W (12 VDC) Max. (H.265+warm light intensity): 6.6 W (12 VDC)

Operating Temperature -40 °C to +60 °C (-40 °F to +140 °F)

Operating Humidity ≤95% Protection IP67

Casing Material Metal + plastic

131.0 mm \times 78.4 mm \times 97.2 mm (5.47" \times 4.80" \times 3.83") (L \times W \times H) **Product Dimensions**

Net Weight 254.5 g (0.56 lb)

What's in the box



Power:

Power Adapter×1

