



Anker Charger (140W 3C1A) with display B2697

Windows displays real-time power for each port, instantly showing if fast charging is activated.

Easily check the power output of each port on the screen, see the remaining power in real-time, and maximize your charger's performance for faster charging.

Worried about your charger overheating? Real-time temperature display and AI temperature control: Monitor and protect your device with real-time temperature data on the smart display, while ActiveShield 2.0 technology provides up to 3 million daily checks. Aerospace-grade Gallium Nitride (GaN) for higher efficiency.

Redesigned ports for better aesthetics & wall mounting.When plugged into the wall, all cables stand vertically to the ground, with the charger's center of gravity closer to the wall, making it less prone to falling and loosening.

The first charger with a window display, offering more possibilities for you to explore: This charger is equipped with an "odometer" function that measures its usage in hours, allowing you to witness its durability firsthand. Moreover, discover features such as the total power interface, real-time power interface for each port, and temperature monitoring page.

140W four-port simultaneous charging for multiple devices: One charger for all your devices. No more worrying about insufficient ports and frequent plugging and unplugging. It supports multiple fast-charging protocols, including PD3.1 and UFCS, making it compatible with a wide range of devices.

Charging Tech	Output Ports	Power per Ports	Total Output Power	Dimension	Weight	Foldable
PD 3.1	3 Type-C 1 USB-A	C1:140W C2:140W C3:40W A:33W	140W	69*69*36mm	275g	Yes



USB-C